

GLADIATOR X COMP LIMITED WARRANTY

100% FREE REPLACEMENT WARRANTY

American Pacific Industries, Inc (API) hereby warrants every new Gladiator X Comp tire bearing a complete description as required by DOT and manufactured AFTER August 1, 2014 (DOT date code 3414) for workmanship and material related conditions for the life of the original tread of a new tire less 2/32". The life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining, at which point the tire is considered to be fully worn out. API will replace the Gladiator X Comp tire with a new Gladiator X Comp tire. All Exclusions listed below void this 100% Free Replacement Warranty. Conditions and coverage are subject to change at any time and without notice.

- A) The worn Gladiator X Comp tire must be replaced with a comparable new Gladiator X Comp tire by an authorized Gladiator X Comp dealer. Copy of invoice will be required.
- B) 100% free replacement applies to new first quality tires only. Retreads, tires unserviceable due to Road Hazard and tires described under Exclusions below are not covered.
- C) Adjustments on ride complaints or out of round tires are excluded from this warranty if they are worn past 2/32" from the original usable tread of the new tire.

EXCLUSIONS

A) All Gladiator X Comp warranties are limited to the original purchaser and the original vehicle on which they are mounted, and are not assignable to subsequent purchasers or vehicles.

B) The warranties listed above are applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the United States and Canada are not covered by these warranties.

C) The following is not covered by the warranties listed above:

- 1) Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
- 2) Failure, damage or irregular wear due to:
- a) fire, accident or vandalism;
- b) mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
- c) misapplication of tire; or
- d) alteration of the tire, addition of foreign material, transfers from one vehicle to another or any previous damages and/or repairs.
- 3) Cost of mounting and balance service.
- 4) Loss of time or use, inconvenience, or any incidental or consequential damages except as prohibited by law.
- 5) Adjustment on out-of-balance or out-of-round tire is allowed only during the first 2/32" of the original tread.

 A set of all four (4) tires from the same vehicle claimed for out-of-round will not be accepted.
- D) Any Gladiator X Comp tire submitted five (5) years or more from the date of manufacture as determined by the DOT Serial number is not covered under the warranties listed above

REPAIRS AND RETREADING: RATING CHANGES AND CAUTIONS

- A) Repaired, retreaded or altered Gladiator X Comp tire with "Speed Rating" no longer retain their "Speed Rating".
- B) If the aforementioned tire(s) is repairable, see the recommended repair procedures used by the tire dealer(s) for repairing tubeless passenger car radial tires as detailed and illustrated in the RMA puncture repair procedures.
- C) Repairs must be restricted to the tread area inside a half inch of the sidewall of the tire.
- D) Do not repair any sidewall punctures and/or tread area punctures that are larger than 1/4" in diameter.

OWNER'S OBLIGATIONS

In order to be eligible for Gladiator X Comp Limited Warranty service, the dealer/owner must:

A) At the time of purchase, the tires must be properly installed, correct air pressure set and the wheels balanced.

Every 6,000 miles the tires must be rotated, proper air pressures set and the wheel alignment checked.

- B) The tire to be adjusted must be presented to an authorized Gladiator X Comp dealer.
- C) Present proof of purchase to the satisfaction of the dealer.
- D) Complete and sign a Gladiator X Comp Warranty Claim Form which is available at any authorized dealer.
- E) Pay the amount due on taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Gladiator X Comp Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specically provided herein.



QUALITY SPEAKS FOR ITSELF ® ENGINEERED TO PERFECTION ®









September 1988 | Septem



PERFORMANCE GUARANTEED®

TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY SINGLE/DUAL (LBS)
X COMP M/T							
31x10.50R15LT	109	Q	6	30.5	10.6	19	2270
35x12.50R15LT	118	Q	8	34.5	12.5	19	2910
LT265/75R16	123/120	Q	10	31.7	10.5	19	3415/3085
LT285/75R16	126/123	Q	10	32.8	11.3	19	3750/3415
LT265/70R17	121/118	Q	10	31.7	10.7	20	3195/2910
33x12.50R17LT	126	Q	10	32.5	12.5	20	3750
35x12.50R17LT	126	Q	10	34.5	12.5	20	3750
37x13.50R17LT	131	Q	10	36.5	13.6	20	4300
40x13.50R17LT	131	Q	10	39.5	13.6	20	4300
33x12.50R18LT	118	Q	10	32.5	12.5	20	2910
35x12.50R18LT	123	Q	10	34.5	12.5	20	3415
33x12.50R20LT	114	Q	10	32.5	12.5	20	2600
35x12.50R20LT	121	Q	10	34.5	12.5	20	3195
37x13.50R20LT	127	Q	10	36.5	13.6	20	3860
33x12.50R22LT	109	Q	10	32.5	12.5	20	2270
35x12.50R22LT	117	Q	10	34.5	12.5	20	2835
37x13.50R22LT	123	Q	10	36.5	13.6	20	3415
35x12.50R24LT	117	Q	10	34.5	12.5	20	2835
37x13.50R24LT	120	Q	10	36.5	13.6	20	3085
37x13.50R26LT	117	Q	10	36.5	13.6	20	2835

AVAILABLE IN 4 NEW X COMP ATR SIZES!

ļ	TIRE SIZE	LOAD INDEX SINGLE/DUAL	SPEED SYMBOL	PLY RATING	OUTSIDE DIAMETER (INCHES)	SECTION WIDTH (INCHES)	TREAD DEPTH (32NDS)	LOAD CAPACITY SINGLE/DUAL (LBS)
	X COMP ATR							
	28x10R14	86	J	10	28	10	20	1165
	30x10R14	90	J	10	30	10	20	1320
	32x10R14	95	J	10	32	10	20	1520
	32X10R15	94	J	10	32	10	20	1475

FEATURES AND BENEFITS

TREAD AND SIDEWALL DESIGN

- Aggressive is an understatement. This tire is a beast!
- Maximum traction and grip on the shoulder area of the tire when it's needed most.
- Self-cleaning tread and shoulder area to prevent mud, rock and snow build up.
- M & S Rated

TIRE CONSTRUCTION ADVANTAGES

- The tire casing has three full plys of polyester with a high turn up on the side wall. This gives the tire excellent strength and durability.
- The tread area has two full steel belts and two full nylon belts.
 The result is a very stable tread and shoulder area for aggressive and proven performance.
- The end result is a tire that is strong, stable, durable and surprisingly quiet.



EC@SAFE

Enthusiast Approved, Race Proven! If you would like to join our race team of

supported drivers, inquire through our contact information on the back!

